

Sun Xtender PVX-6240T

Solar Battery Manufactured by: Concorde Battery Corporation

Description of Solar Battery:

VRLA-AGM Deep Cycle Battery for Off Grid and Grid Tied Systems.

Sun Xtender batteries provide safe, reliable and long lasting power.

Environmentally friendly, there is no exposed lead on Sun Xtender batteries
100 percent recyclable
Sustainable, Clean, Renewable Energy Storage.

Since 1987, Sun Xtender solar batteries have been hand crafted for quality in the U.S.A. Valve regulated lead acid batteries with AGM construction (VRLA-AGM) is the original AGM design adopted by the military. Non-spillable construction prohibits any electrolyte leaking or spewing, allowing the battery to be used upright or on its end or side. The maintenance free AGM design means no water replenishment - ever.

Utilizing pure lead calcium grids, the Sun Xtender battery plates are thicker than the industry standard for longer cycle life, increased reliability and power. The low impedance AGM design allows for excellent charge acceptance and there is no current limit required with controlled voltage charging.

The Sun Xtender Battery product line features proprietary PolyGuard™ Microporous Polyethylene Separators, shielding the positive plates against shorting, shock or vibration. No other manufacturers offer this dual layer insulation protection feature.

Sun Xtender Battery covers and containers are uniquely molded with high impact, reinforced copolymer polypropylene and are designed with thick end walls to prevent bulging. The copper alloy T Terminals are corrosion resistant and are supplied with silicon bronze bolts and washers.

All Sun Xtender Batteries ship Hazmat Exempt.

PVX-6240T

Voltage		2v					
Battery Series		2 Volt Sun Xtender Series					
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 Volts per cell - 24 Hour Rate		624 Ah					
Weight		65 lb / 29.5 kg					
Sun Xtender® Solar Battery Part Number	Length		Width		Height		
	in	mm	in	mm	in	mm	
PVX-6240T	12.01	305	6.60	168	8.93	227	
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 volts per cell							
1 Hr Rate	2 Hr Rate	4 Hr Rate	8 Hr Rate	24 Hr Rate	48 Hr Rate	72 Hr Rate	120 Hr Rate
390 Ah	492 Ah	510 Ah	558 Ah	624 Ah	672 Ah	696 Ah	720 Ah

Specifications subject to change without notice.

