

# **Sun Xtender PVX-6720T**

## **Solar Battery Manufactured by: Concorde Battery Corporation**

### **Description of Solar Battery:**

VRLA-AGM Deep Cycle Battery for Off Grid and Grid Tied Systems.

Recombinant gas Sun Xtender® Series solar batteries are low resistance, valve regulated lead acid (VRLA) batteries.

- Designed for photovoltaic applications for superior & reliable solar power
- "T" terminals are copper alloy with silicon bronze bolts, nuts, & washers
- Low impedance design
- Maintenance free
- No addition of electrolyte or water required
- Will not spill electrolyte in any attitude
- Shipped fully charged and ready to install
- Manufactured with absorbed glass mat separators (AGM)
- Sun Xtender® Series batteries ship non-HAZMAT

**PVX-6720T**

Voltage		2v					
Battery Series		<a href="#">2 Volt Sun Xtender Series</a>					
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 Volts per cell - 24 Hour Rate		672 Ah					
Weight		70 lb / 31.8 kg					
Sun Xtender® Solar Battery Part Number	Length		Width		Height		
	in	mm	in	mm	in	mm	
PVX-6720T	10.28	261	7.06	179	9.92	252	
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 volts per cell							
1 Hr Rate	2 Hr Rate	4 Hr Rate	8 Hr Rate	24 Hr Rate	48 Hr Rate	72 Hr Rate	120 Hr Rate
429 Ah	540 Ah	555 Ah	612 Ah	672 Ah	738 Ah	768 Ah	789 Ah

Specifications subject to change without notice.

