



Safety Data Sheet (SDS)

1. IDENTIFICATION

Issue Date: 06/01/2015, SDS # 003, Version #: 01

Product Name	Non-Spillable Battery
Synonyms	Valve Regulated Lead Acid Battery. (UN/ID No.: UN2800)
Product Use	Vehicle Electrical System
Manufacturer / Supplier / Address	Yacht Battery Co., Ltd. 4F-5, No. 925, Sec. 4, Taiwan Blvd., Taichung, 40767 Taiwan, R.O.C. Yacht Technology (Vietnam), Co., Ltd. Lot_A9H_CN, Bau Bang Industrial Park, Bau Bang District, Binh Duong Province, Vietnam www.yacht-battery.com
Transportation Emergency Number	Infotrac (24-Hour Emergency Contact Number) 1-800-535-5053 (North America) 1-352-323-3500 (International)

NOTE: The Yacht battery is considered an article as defined by 29 CFR 1910.1200 (OSHA Hazard Communication Standard). The information contained in this SDS is supplied at the customer's request for information only.

2. GHS HAZARD(S) IDENTIFICATION

Classification:

Health Hazards	Not classified
Physical hazards	Not classified
OSHA Regulatory Status	Material is an article. No health effects are expected related to normal use of this product as sold. Hazardous exposure can occur only when the product is heated, oxidized or otherwise processed or damaged to create lead dust, vapor or fume. Follow manufacturer's instructions for installation, service and use.

GHS Label Elements:

Emergency Overview		
Appearance	Physical state	Odor
Not available.	Solid	Odorless

3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS (Chemical / Common Names)	CAS Number	% by Weight
Inorganic Lead / Lead Compounds	7439-92-1	60-85
Electrolyte (H ₂ SO ₄ / H ₂ O)	7664-93-9	10-28
Tin	7440-31-5	<0.01
Arsenic	7440-38-2	<0.01

Composition Comments: All concentrations are in percent by weight.

4. FIRST AID MEASURES

Note: Under normal conditions of battery use, internal components will not present a health hazard. The following information is provided for battery electrolyte (acid) and lead for exposures that may occur during battery production or container breakage or under extreme heat conditions such as fire.

Inhalation	<ul style="list-style-type: none"> Sulfuric Acid: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult a physician. Lead: Remove from exposure, gargle, wash nose and lips; consult physician.
-------------------	---



Safety Data Sheet (SDS)

Skin contact	<ul style="list-style-type: none"> • <u>Sulfuric Acid:</u> Flush with large amounts of water for at least 15 minutes; remove contaminated clothing completely, including shoes. If symptoms persist, seek medical attention. • <u>Lead:</u> Wash immediately with soap and water.
Eye contact	<ul style="list-style-type: none"> • <u>Sulfuric Acid and Lead:</u> Flush immediately with large amounts of water for at least 15 minutes while lifting lids; Seek immediate medical attention if eyes have been exposed directly to acid.
Ingestion	<ul style="list-style-type: none"> • <u>Sulfuric Acid:</u> Give large quantities of water; Do NOT induce vomiting or aspiration into the lungs may occur and can cause permanent injury or death; consult physician. • <u>Lead:</u> Consult physician immediately.
Self-protection of the first aider	Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. FIRE FIGHTING MEASURES

Extinguishing Media	CO2; foam; dry chemical. Do not use carbon dioxide directly on cells. Avoid breathing vapors. Use appropriate media for surrounding fire.
Special Fire Fighting Procedures	Use positive pressure, self-contained breathing apparatus. Beware of acid splatter during water application and wear acid-resistant clothing, gloves, face and eye protection. If batteries are on charge, shut off power to the charging equipment, but note that strings of series connected batteries may still pose risk of electric shock even when charging equipment is shut down.
Unusual Fire and Explosion Hazard	Highly flammable hydrogen gas is generated during charging and operation of batteries. If ignited by burning cigarette, naked flame or spark, may cause battery explosion with dispersion of casing fragments and corrosive liquid electrolyte. Carefully follow manufacturer's instructions for installation and service. Keep away all sources of gas ignition and do not allow metallic articles to simultaneously contact the negative and positive terminals of a battery. Follow manufacturer's instructions for installation and service.

6. ACCIDENTAL RELEASE MEASURES

Protective Measures to be Taken if Material is Released or Spilled	Stop flow of material, contain / absorb small spills with dry sand, earth, and vermiculite. Do not use combustible materials. If possible, carefully neutralize spilled acid with soda ash, sodium bicarbonate, lime, etc. Wear acid-resistant clothing, boots, gloves, and face shield. Do not allow discharge of unneutralized acid to sewer. Acid must be managed in accordance with approved local, state, and federal requirements. Consult state environmental agency and / or federal EPA.
Waste Disposal Method	Dispose of as a hazardous waste. Dispose of in accordance with applicable local, state and federal regulations.
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas. Runoff from fire control and dilution water may be toxic and corrosive and may cause adverse environmental impacts. See Section 12 for additional ecological information.



Safety Data Sheet (SDS)

7. HANDLING AND STORAGE

Handling	Unless involved in recycling operations, do not breach the casing or empty the contents of the battery. Handle carefully and avoid tipping, which may allow electrolyte leakage. There may be increasing risk of electric shock from strings of connected batteries. Keep containers tightly closed when not in use. If battery case is broken, avoid contact with internal components. Keep vent caps on and cover terminals to prevent short circuits. Place cardboard between layers of stacked batteries to avoid damage and short circuits. Keep away from combustible materials, organic chemicals, reducing substances, metals, strong oxidizers and water. Use banding or stretch wrap to secure items for shipping.
Storage	Store frost-free under roof; prevent short circuits. Do not store in sealed, unventilated areas. Seek agreement with local water authorities in case of larger quantities. Avoid overheating and charging. Do not use organic solvents or anything other than manufacturers recommended cleaners on the batteries. If batteries have to be stored in storage rooms, it is imperative that the instructions for use are observed.
Incompatible materials	<ul style="list-style-type: none"> • Sulfuric Acid: Contact with combustible and organic materials may cause fire and explosion. Also reacts violently with strong reducing agents, metals, sulfur trioxide, strong oxidizers and water. Contact with metals may product toxic sulfur dioxide fumes and may release flammable hydrogen gas. • Lead compounds: Avoid contact with strong bases, acids, combustible organic materials, halides, halogenates, potassium nitrate, permanganate, peroxides, nascent hydrogen, reducing agents, and water.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits (mg/m³)

Ingredients	CAS Number	OSHA PEL	ACGIH	US NIOSH	Quebec PEV	Ontario OEL	EU OEL
Lead, inorganic	7439-92-1	0.05	0.05	0.05	0.05	0.05	0.15 (a)
Tin	7440-31-5	2	2	2	-	-	-
Arsenic	7440-38-2	0.01	0.01	0.01	-	-	-
Electrolyte (H ₂ SO ₄ / H ₂ O)	7664-93-9	1	0.2	1	1	0.2	0.05 (b)

NOTES:

(a) As inhalable aerosol

(b) Thoracic fraction

• OSHA:

Lead - US OSHA Specifically Regulated Substances (29 CFR 1910.1001 – 1050)

Sulfuric Acid - US OSHA Table Z-1 Limits for Air Contaminants (29CFR 1910.1000)

• ACGIH: US ACGIH Threshold Limit Values

• NIOSH: US NIOSH Pocket Guide to Chemical Hazards

Exposure Guidelines:

The OELs listed above are only applicable if the internal components of the battery cell are released. Follow standard monitoring procedures.



Safety Data Sheet (SDS)

Engineering Controls (Ventilation)	Store Non-Spillable Battery at ambient temperature. Never recharge batteries in an unventilated, enclosed space. Do not subject product to open flame or fire. Avoid conditions that could cause arcing between terminals. The health hazard risks of handling this material are dependent on factors, such as physical form and quantity. Site-specific risk assessments should be conducted to determine the appropriate exposure control measures. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels as low as reasonably achievable.
Respiratory Protection (NIOSH / MSHA approved)	NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT. When concentrations of sulfuric acid mist are known to exceed PEL, use NIOSH or MSHA-approved respiratory protection.
Skin Protection	NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT. If battery case is damaged, use rubber or plastic acid-resistant gloves with elbow-length gauntlet, acid-resistant apron, clothing and boots.
Eye Protection	NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT. If necessary to handle damaged product where exposure to the organic electrolyte is a possibility, chemical splash goggles and a face shield are recommended.
General Hygiene Considerations	When using, do not eat, drink, or smoke. Wash hands after handling. Contaminated work clothing should not be allowed out of the workplace. Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor	Manufactured article; no apparent odor.
Odor Threshold	Not applicable
pH	Not applicable
Melting Point	Lead – 621.32 °F (327.4 °C) Not applicable unless individual components exposed.
Boiling Point	Battery Electrolyte (Acid) – 230 - 233.6 °F (110 - 112 °C) Lead – 3180 °F (1749 °C) Not applicable unless individual components exposed.
Flash Point	Not applicable
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Vapor Pressure (mm Hg @ 20 ° C)	Battery Electrolyte (Acid) 11.7
Upper / lower flammability or explosive limits	Hydrogen Flammability Limit Lower – 4.1 % Flammability Limit Upper – 74.2 %
Vapor Pressure	10.95 mm Hg (Sulfuric Acid)
Vapor Density	Not applicable
Relative Density	1.21 - 1.3 Battery Electrolyte (Acid)
Solubility	Lead and Lead dioxide are not soluble. 100 % Battery Electrolyte (Acid).
% Volatile by Weight	Not applicable unless individual components exposed.
Partition coefficient (n-octanol / water)	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not applicable
Viscosity	Not applicable
Density	11.35 g/cm ³ Lead



Safety Data Sheet (SDS)

10. STABILITY AND REACTIVITY

Reactivity	This product is non-reactive under normal conditions or use, storage, and transport.
Stability	Non-Spillable Batteries are considered stable.
Conditions to Avoid	Sparks and other sources of ignition; high temperature; over charging.
Incompatibility (materials to avoid)	<ul style="list-style-type: none"> • <u>Acid:</u> Contact with combustibles and organic materials may cause fire and explosion. Also reacts violently with strong reducing agents, metals, sulfur trioxide gas, strong oxidizers, and water. Contact with metals may produce toxic sulfur dioxide fumes and may release flammable hydrogen gas. • <u>Lead compounds:</u> Avoid contact with strong acids, bases, halides, halogenates, potassium nitrate, permanganate, peroxides, nascent hydrogen, and reducing agents.
Hazardous Decomposition Products	<ul style="list-style-type: none"> • <u>Acid:</u> Sulfur trioxide, carbon monoxide, sulfuric acid mist, sulfur dioxide, hydrogen sulfide. • <u>Lead compounds:</u> Temperatures above the melting point are likely to produce toxic metal fume, vapor, or dust; contact with strong acid or base or presence of nascent hydrogen may generate highly toxic arsine gas.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

ROUTES AND METHODS OF ENTRY

Inhalation	<ul style="list-style-type: none"> • <u>Sulfuric Acid:</u> Breathing of sulfuric acid vapors or mists may cause severe respiratory irritation. • <u>Lead Compounds:</u> Inhalation of lead dust or fumes may cause irritation of upper respiratory tract and lungs.
Skin Contact	<ul style="list-style-type: none"> • <u>Sulfuric Acid:</u> Severe irritation, burns and ulceration. • <u>Lead Compounds:</u> Not absorbed through the skin.
Skin Absorption	In the event of overcharging or damage to the unit, exposure to organic electrolyte solution / mist is possible. Extreme exposures to the organic electrolyte can be absorbed through the skin.
Eye Contact	<ul style="list-style-type: none"> • <u>Sulfuric Acid:</u> Severe irritation, burns, cornea damage, and blindness. • <u>Lead Compounds:</u> May cause eye irritation.
Ingestion	<ul style="list-style-type: none"> • <u>Sulfuric Acid:</u> May cause severe irritation of mouth, throat, esophagus and stomach. • <u>Lead Compounds:</u> Acute ingestion may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping. This may lead rapidly to systemic toxicity and must be treated by a physician.

EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE.



Safety Data Sheet (SDS)

SIGNS AND SYMPTOM OF OVEREXPOSURE

Acute Effects	<ul style="list-style-type: none"> • <u>Sulfuric Acid:</u> Severe skin irritation, damage to cornea, upper respiratory irritation. • <u>Lead Compounds:</u> Symptoms of toxicity include headache, fatigue, abdominal pain, loss of appetite, muscular aches and weakness, sleep disturbances and irritability.
Chronic Effects	<ul style="list-style-type: none"> • <u>Sulfuric Acid:</u> Possible erosion of tooth enamel, inflammation of nose, throat & bronchial tubes. • <u>Lead Compounds:</u> Anemia; neuropathy, particularly of the motor nerves, with wrist drop; kidney damage; reproductive changes in males and females. Repeated exposure to lead and lead compounds in the workplace may result in nervous system toxicity. Some toxicologists report abnormal conduction velocities in persons with blood lead levels of 50 µg/100 ml or higher. Heavy lead exposure may result in central nervous system damage, encephalopathy and damage to the blood-forming (hematopoietic) tissues.

EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Overexposure to sulfuric acid mist may cause lung damage and aggravate pulmonary conditions. Contact of sulfuric acid with skin may aggravate diseases such as eczema and contact dermatitis. Lead and its compounds can aggravate some forms of kidney, liver and neurologic diseases.

ADDITIONAL HEALTH DATA

All heavy metals, including the hazardous ingredients in this product, are taken into the body primarily by inhalation and ingestion. Most inhalation problems can be avoided by adequate precautions such as ventilation and respiratory protection covered in Section 8. Follow good personal hygiene to avoid inhalation and ingestion: wash hands, face, neck and arms thoroughly before eating, smoking or leaving the work site. Keep contaminated clothing out of non-contaminated areas, or wear cover clothing when in such areas. Restrict the use and presence of food, tobacco and cosmetics to non-contaminated areas. Work clothes and work equipment used in contaminated areas must remain in designated areas and never taken home or laundered with personal non-contaminated clothing. This product is intended for industrial use only and should be isolated from children and their environment.

The 19th Amendment to EC Directive 67/548/EEC classified lead compounds, but not lead in metal form, as possibly toxic to reproduction. Risk phrase 61: May cause harm to the unborn child, applies to lead compounds, especially soluble forms.

Toxicological Data

Constituents	Lead (CAS 7439-92-1)	Sulfuric Acid (CAS 7664-93-9)
Species	Rat	Rat
Test Results	1050 ug/kg	2140 mg/kg
Acute oral toxicity	TDLo	LD50
Skin corrosion / irritation	Electrolyte: Causes severe skin burns	
Serious eye damage / eye irritation	Electrolyte: Causes severe eye damage	
Respiratory Sensitization	Not Classified	
Skin Sensitization	Not a skin sensitizer	
Germ Cell Mutagenicity	No data available	



Safety Data Sheet (SDS)

CARCINOGENICITY

Under normal handling and storage conditions, the exposure to carcinogenic components is not expected. Risk of adverse effects occurs only if the cell is mechanically, thermally, or electrically abused to the point of compromising the enclosure.

- Sulfuric Acid:

The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mist containing sulfuric acid" as a Category I carcinogen, a substance that is carcinogenic to humans. This classification does not apply to liquid forms of sulfuric acid or sulfuric acid solutions contained within a battery. Inorganic acid mist (sulfuric acid mist) is not generated under normal use of this product. Misuse of the product, such as overcharging, may result in the generation of sulfuric acid mist.

- Lead Compounds:

Lead is listed as a 2B carcinogen, likely in animals at extreme doses. Proof of carcinogenicity in humans is lacking at present.

Carcinogenic Effects			
	CAS Number	IARC	NTP
Sulfuric acid	7664-93-9	Group 1-Carcinogenic	Not established
Lead	7439-92-1	Group 2B-Possibly carcinogenic to humans.	Reasonably anticipated to be human carcinogen

- **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050 / 1200)**

Not listed.

Reproductive toxicity	May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	No data available.
Specific target organ toxicity - repeated exposure	<u>Lead:</u> May cause damage to organs (blood, central nervous system) through prolonged or repeated exposure.
Aspiration hazard	Not classified.

12. ECOLOGICAL INFORMATION

- **Environmental Fate**

Lead is very persistent in soil and sediments. No data on environmental degradation. Mobility of metallic lead between ecological compartments is slow. Bioaccumulation of lead occurs in aquatic and terrestrial animals and plants but little bioaccumulation occurs through the food chain. Most studies include lead compounds and not elemental lead.

- **Ecotoxicity**

Very toxic to aquatic life with long lasting effects. However, no ecological impacts expected under normal use conditions.

Constituents	Inorganic Lead / Lead Compounds (CAS 7439-92-1)
Species	Rainbow trout, Donaldson trout (<i>Oncorhynchus mykiss</i>)
Test Results	1.17 mg/l, 96 hours
Aquatic	Fish LC50
Persistence and Degradability	No data available
Bioaccumulative potential	No data available
Additional Information	No known effects on stratospheric ozone depletion Volatile organic compounds: 0% (by Volume) Water Endangering Class (WGK): NA



Safety Data Sheet (SDS)

13. DISPOSAL CONSIDERATIONS

Waste disposal method	Material should be recycled if possible. Lead-acid batteries are completely recyclable. Product can be recycled along with automotive (SLI) lead-acid batteries. Dispose waste and residues in accordance with applicable federal, state, and local regulations.
Hazardous waste code	D008: Lead
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or packaging may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

Yacht's VRLA batteries have passed vibration, pressure differential and free flowing acid tests under CFR 49 173.159(d) and meet IATA Special Provisions A48 and A67. The batteries are securely packaged, protected from short circuits and labeled "Non-Spillable." Vision's VRLA batteries are suitable for DOT Hazardous Material Regulations and IATA Dangerous Goods Regulation and meet the special provision 238. in IMDG code.

Ground-US Dot	Not regulated as a hazardous material. Yacht VRLA batteries have been tested and meet the non-spillable criteria listed in CFR 49, 173.159 (d) (3) (i) and (ii). Non-spillable batteries are excepted from CFR 49, Subchapter C requirements, provided that the following criteria are met. 1. The batteries must be protected against short circuits and securely packaged. 2. The batteries and their outer packaging must be plainly and durably marked "NON-SPILLABLE" or "NONSPILLABLE BATTERY".
Aircraft-ICAO-IATA	Not regulated as a hazardous material. Yacht VRLA Batteries have been tested and meet the non-spillable criteria listed in IATA Packing Instruction 872 and Special Provision A67. These batteries are excepted from all IATA regulations provided that the battery terminals are protected against short circuits. The words "Not Restricted, as per Special Provision A67" must be included in the description on the Air Waybill.
Vessel-IMO-IMDG	Not regulated as a hazardous material. Yacht VRLA Batteries have been tested and meet the non-spillable criteria listed in IMDG Code Special Provision 238 1 and 2, therefore, are not subject to the provision of the IMDG Code provided that the battery terminals are protected against short circuits when packaged for transport.
TDG	These batteries have been tested and meet the non-spillable criteria. Non-spillable batteries are excepted provided that the following criteria are met: 1.) The batteries must be protected against short circuits and securely packaged. 2.) The batteries and their outer packaging must be plainly and durably marked "NON-SPILLABLE" or "NON SPILLABLE BATTERY".
MEX	Not regulated
ICAO (air)	Yacht VRLA batteries have been tested and meet the non-spillable criteria listed in IATA Packing Instruction 872 and Special Provision A67. These batteries are excepted from all IATA regulations provided that the battery terminals are protected against short circuits. The words "Not Restricted, as per Special Provision A67" must be included in the description on the Air Waybill.



Safety Data Sheet (SDS)

ADR / RID	Non-spillable batteries are not subject to the requirements of ADR if, at a temperature of 55C, the electrolyte will not flow from a ruptured or cracked case and there is no free liquid to flow and if, as packaged for carriage, the terminals are protected from short circuit.
ADN	Not regulated

UN NO.	2800
IMO Class	8
Proper shipping name (PSN)	BATTERY WET NON-SPILLABLE
Packing group	III
Marine Pollutant	No

15. REGULATORY INFORMATION

This product is an article pursuant to 29 CFR 1910.1200 and as such is not subjected to the OSHA Hazard Communication Standard.

TSCA

Ingredients listed in the TSCA registry are lead, lead compounds, and sulfuric acid.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Lead (CAS 7439-92-1)	Reproductive toxicity Central nervous system Kidney Blood Acute toxicity
----------------------	--

CERCLA Hazardous Substance List (40 CFR 302.4)

Lead (CAS 7439-92-1)	LISTED
Sulfuric Acid (CAS 7664-93-9)	LISTED

EPCRA Section 302 Extremely hazardous substance

Chemical Name	CAS Number	Weight-%	Reportable Quantity	Threshold Planning Quantity
Sulfuric Acid	7664-93-9	30-40	1000 lb EPCRA RQ	1000 lb TPQ
Water	7732-18-5	60-70	Not Listed	Not Listed

- EPCRA Section 311 / 312 Hazard Categorization**

EPCRA Section 312 Tier Two reporting is required for non-automotive batteries if sulfuric acid is present in quantities of 500 lbs. or more and / or if lead is present in quantities of 10,000 lbs. or more. For more information consult 40 CFR 370.10 and 40 CFR 370.40.

- EPCRA Section 313 Toxic Substances**

40 CFR section 372.38 (b) states: If a toxic chemical is present in an article at a covered facility, a person is not required to consider the quantity of the toxic chemical present in such article when determining whether an applicable threshold has been met under § 372.25, § 372.27, or § 372.28 or determining the amount of release to be reported under § 372.30. This exemption applies whether the person received the article from another person or the person produced the article. However, this exemption applies only to the quantity of the toxic chemical present in the article.

Chemical Name	CAS Number	% by Weight
Lead	7439-92-1	60-85



Safety Data Sheet (SDS)

Other Federal Regulations

Lead (CAS 7439-92-1)	Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
Sulfuric Acid (CAS 7664-93-9)	Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

- **Safe Drinking Water Act (SDWA)**
Not regulated
- **Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**
Sulfuric Acid (CAS 7664-93-9), 6552
- **Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**
Sulfuric Acid (CAS 7664-93-9), 20 % WV
- **DEA Exempt Chemical Mixtures Code Number**
Sulfuric Acid (CAS 7664-93-9), 6552

US State Regulations

Lead (CAS 7439-92-1) Sulfuric Acid (CAS 7664-93-9)	US Massachusetts RTK – Substance List
	US New Jersey Worker and Community Right-to-know Act
	US Pennsylvania Worker and Community Right-to-know Law
	US Rhode Island RTK

- **US California Proposition 65**
WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **Wash hands after handling.**
* Battery companies not party to the 1999 consent judgment with Mateel Environmental Justice Foundation should include a Proposition 65 Warning that complies with the current version of Proposition 65.
- **US California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Chemical Name	CAS Number	% by Weight
Lead	7439-92-1	60-85
Sulfuric Acid	7664-93-9	10-28
Arsenic (as arsenic oxides)	7440-38-2	<0.01

International Inventories

Country(s) or Region	Inventory Name	On inventory (yes / no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

- * A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).
- A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

- **Canadian Domestic Substance List (DSL)**
All ingredients remaining in the finished product as distributed into commerce are included on the Domestic Substances List.

WHMIS Classifications

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the Controlled Products Regulations.

NPRI and Ontario Regulation 127/01

This product contains the following chemicals subject to the reporting requirements of Canada NPRI +/- or Ont. Reg. 127/01:

Chemical Name	CAS Number	% by Weight
Lead	7439-92-1	60-85



Safety Data Sheet (SDS)

• **European Inventory of Existing Commercial Chemical Substances (EINECS)**

All ingredients remaining in the finished product as distributed into commerce are exempt from, or included on, the European Inventory of Existing Commercial Chemical Substances.

REACH: Contains more than 0.1% lead monoxide. Lead Monoxide (CAS: 1317-36-8) is listed as a substance of very high concern (SVHC) under EU REACH regulation annex XIV.

European Communities (EC) Hazard Classification according to directives 67/548/EEC and 1999/45/EC.

R-Phrases	S-Phrases
23/25	1/2, 20/21, S28

ENCS

Japan Existing and New Chemical Substances

IECSC

China Inventory of Existing Chemical Substances

KECL

Korean Existing and Evaluated Chemical Substances


PICCS

Philippines Inventory of Chemicals and Chemical Substances

AICS

Australian Inventory of Chemical Substances

16. OTHER INFORMATION

Issue Date	06/01/2015
Revision Date	-
Version #	01
Further information	NFPA Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe
NFPA ratings	

DISCLAIMER:

This Safety Data Sheet is based upon information and sources available at the time of preparation or revision date. Information in the SDS was obtained from sources which we believe are reliable, but are beyond our direct supervision or control. We make no Warranty of Merchantability, Fitness for any particular purpose or any other Warranty, Expressed or Implied, with respect to such information and we assume no liability resulting from its use. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. It is the obligation of each user of this product to determine the suitability of this product and comply with the requirements of all applicable laws regarding use and disposal of this product. For additional information concerning Yacht Battery Co., Ltd. products or questions concerning the contents of this SDS please contact your Yacht representative.