



955 Todd Avenue Azusa, CA 91702 | Tel. 626-969-6886 | Fax 626-969-8566



[Lifeline Home](#)



[Marine Batteries](#)



[RV Batteries](#)

[Racing Batteries](#)



[OEMs & Pro Users](#)

[Lifeline Battery Distributors](#)

[Lifeline Technical Manual](#)

Lifeline 6 Volt Battery.....stronger & longer life. -

O.H., North Carolina USA ---> [Add Your Quote here](#) [See more Lifeline Battery Satisfied User Quotes](#)

AGM Deep Cycle RV Batteries From Lifeline Battery Corporation

- [RV Battery Main](#)
- [Deep Cycle RV Battery Specifications](#)
- [Starting RV Battery Specifications](#)
- [RV Battery Sizing Calculator DC-DC](#)
- [RV Battery Sizing Calculator AC-DC](#)
- [RV Battery Distributors](#)
- [RV Battery Manual](#)



[Material Safety Data Sheet](#)






DEEP CYCLE MARINE BATTERY APPLICATIONS












[Click here to view Starting RV Batteries](#)

To get to specific rv battery information click on the part number.

[Click to get specific terminal information for all Lifeline RV batteries](#)

[PRINT THIS PAGE](#)

Lifeline Battery Part Number ▲▼	Volts	RV Battery Dimensions						Weight lb - kg ▲▼	Cold Cranking Amps 68° F 32° F 0° F ▲▼ ▲▼ ▲▼			Rated Cap. Hrs 20 Hr Rate ▲▼	Minutes of Discharge 25 15 8 AmpsAmpsAmps ▲▼ ▲▼ ▲▼			
		Length in mm ▲▼	Width in mm ▲▼	Height in mm ▲▼	Weight lb - kg ▲▼	68° F ▲▼	32° F ▲▼		0° F ▲▼	25 Amps ▲▼	15 Amps ▲▼		8 Amps ▲▼			
GPL-U1T 	12v	7.71	195.90	5.18	132.00	6.89	175.00	24.00	10.90	325	275	215	33	50	93	185
GPL-24T 	12v	11.13	282.70	6.60	167.60	9.25	234.80	56.00	25.50	800	680	550	80	149	259	524
GPL-27T 	12v	13.09	332.50	6.60	167.60	9.25	234.80	65.00	29.50	845	715	575	100	186	324	655
GPL-31T 	12v	12.90	327.80	6.75	171.30	9.27	235.50	69.00	31.40	880	750	600	105	195	340	688
GPL-30HT 	12v	13.46	342.00	6.77	172.00	11.95	304.00	96.00	43.50	1000	850	700	150	315	555	1120

GPL-4DA		12v	20.76	527.40	8.70	221.00	8.63	219.10	135.00	61.20	1595	1360	1100	210	390	680	1375
GPL-4DL		12v	20.76	527.40	8.70	221.00	8.63	219.10	135.00	61.20	1595	1360	1100	210	390	680	1375
GPL-8DA		12v	20.76	527.30	10.89	276.60	8.60	218.40	162.00	73.60	1975	1675	1350	255	475	825	1670
GPL-8DL		12v	20.76	527.30	10.89	276.60	8.60	218.40	162.00	73.60	1975	1675	1350	255	475	825	1670
GPL-4CT		6v	10.28	261.10	7.06	179.30	9.92	252.00	66.00	30.00	1095	925	750	220	492	856	1692
GPL-6CT		6v	10.28	261.00	7.06	179.30	12.94	329.00	90.00	40.80	1150	1025	925	300	692	1200	2205
GPL-L16T		6v	11.64	296.00	6.95	177.00	15.73	399.00	119.00	54.00	1975	1675	1350	400	950	1625	3195
GPL-L16T-2V		2v	11.64	296.00	6.95	177.00	15.73	399.00	119.00	54.00	5332	4552	3645	1200	2850	4875	9585
GPL-31T-2V		2v	12.90	327.80	6.75	171.30	9.27	235.50	69.00	31.40	4752	4050	3240	630	1170	2040	4128
GPL-4CT-2V		2v	10.28	261.10	7.06	179.30	9.92	252.00	66.00	30.00	2950	2500	2025	660	1476	2568	5076
GPL-6CT-2V		2v	10.28	261.00	7.06	179.30	12.94	329.00	90.00	40.80	3100	2750	2500	900	2076	3600	6615

Lifeline Battery Terminal Types

Part Number

GPL-24T, GPL2400T, GPL27T,
GPL-2700T, GPL-31T, GPL-3100T

GPL-4DL, GPL-8DL

GPL-4DA, GPL-8DA

GPL-4CT, GPL-6CT, GPL-1400T

GPL-U1T

Terminal Types

Marine Terminal (Copper Alloy)
Pos Terminal=M10 & Neg Terminal =M8

L-Blade Terminal (Solid Copper) w/M8 Hardware

A- SAE Post Automotive (Lead Alloy)

M8 Threaded Insert (Copper Alloy)

M6 Threaded Insert (Copper Alloy)

- Optional Terminals:** GPL-4CT & GPL-6CT are available (special order) with Marine Terminals.
- Metric/U.S sizes:** Nearest U.S. Dimentsions: M6 = 1/4", M8 = 5/16", M10 = 3/8" (U.S. reference sizes only, not interchangeable).
- Torque Values:** (M6 use 35 in-lbs / 4.0 Nm) (M8 & M10 use 70 in-lbs / 7.9 Nm)
- Terminal Hardware:** When required, all batteries are supplied with silicon bronze bolts, nuts & washers necessary for installation.
- Handles:** All part numbers include carrying or lifting handles.
- Ratings:** Capacity ratings are after 15 cycles & are at 77°F (25°C) to 1.75 volts per cell.
- Note:** Never install batteries in an unventilated compartment or a sealed compartment or sealed container

NOTICE: The technical data contained herein has been reviewed and approved for general release on the basis that it contains no export controlled information. No part of this site may be copied or reproduced by any means, including electronic or mechanical, without written permission from Concorde Battery Corporation and Lifeline Batteries.

DISCLAIMER: The technical data contained herein is based upon the best information available as of the latest revision date. Concorde Battery Corporation the Manufacturer of Lifeline Batteries, makes no warranty of merchantability, fitness for any particular purpose, or any other warranty, expressed or implied, with respect to such information. Both Concorde Battery and Lifeline Battery assume no liability resulting from its use. It is the obligation of each user of the product to determine the suitability for any particular application and to comply with the requirements of all applicable laws regarding use and disposal of this product.

Home Page - Site Map - ISO9001:2000 + AS9100B(pdf) - Battery Transportation Information- MSDS
Aircraft Batteries - Solar Batteries

Racing Batteries - AGM Battery Directory - Business Hours - Upcoming Events / Trade Shows - Contact Us

LIFELINE MARINE & RV BATTERIES

955 Todd Avenue
Azusa, CA 91702

Tel. 626-969-6886
Fax 626-969-8566

