

Sun Xtender PVX-1180T

Solar Battery Manufactured by: Concorde Battery Corporation

Description of Solar Battery:

VRLA-AGM Deep Cycle Battery for Off Grid and Grid Tied Systems.

Sun Xtender pioneered renewable energy storage batteries for Off Grid and Grid Tied Systems.

Since 1987, Sun Xtender has been designing valve regulated lead acid batteries with AGM construction (VRLA-AGM). The non-spillable construction allows the battery to be used upright or on its end or side and the maintenance free AGM design means no water replenishment ever.

Utilizing pure lead calcium grids, the plates are thicker than the industry standard for longer cycle life, increased reliability and power. The low impedance AGM design allows for excellent charge acceptance and there is no current limit required with controlled voltage charging.

The Sun Xtender product line features proprietary PolyGuard® Microporous Polyethylene Separators, shielding the positive plates against shorting, shock or vibration. No other manufacturer offers this dual layer insulation with its effective protection feature.

Sun Xtender battery covers and containers are uniquely molded with high impact, reinforced copolymer polypropylene and are designed with thick end walls to prevent bulging. The copper alloy T Terminals are corrosion resistant and are supplied with silicon bronze bolts and washers.

All SunXtender Batteries ship Hazmat Exempt.

See the Sun Xtender Battery Technical Manual for details on applications and specifications.

PVX-1180T applications include Traffic Arrow / Message Boards, Cathodic Protection, Grid Tied & Off Grid Homes, SCADA, Medical Refrigeration Clinics, Power for Remote Areas / Developing Nations, Microwave Earth / Satellite Stations, Parking Lot Lighting.

PVX-1180T

Voltage	12v						
Battery Series	12 Volt Sun Xtender Series						
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 Volts per cell - 24 Hour Rate	118 Ah						
Weight	72 lb / 32.7 kg						
Sun Xtender® Solar Battery Part Number	Length		Width		Height		
	in	mm	in	mm	in	mm	
PVX-1180T	12.90	328	6.75	171	8.96	228	
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 volts per cell							
1 Hr Rate	2 Hr Rate	4 Hr Rate	8 Hr Rate	24 Hr Rate	48 Hr Rate	72 Hr Rate	120 Hr Rate
72 Ah	92 Ah	95 Ah	104 Ah	118 Ah	128 Ah	133 Ah	137 Ah

Specifications subject to change without notice.

