

### 1. IDENTIFICATION

#### Issue Date: 06/01/2015, SDS # 004, Version #: 01

Product Name	Battery Acid	
Synonyms	Battery Electrolyte (Acid), Sulfuric Acid (Dilute)	
Product Use	Used to Activate Dry Batteries	
Manufacturer / Supplier / Address	Yacht Battery Co., Ltd.	
	4F-5, No. 925, Sec. 4, Taiwan Blvd., Taichung, 40767 Taiwan, R.O.C.	
	Yacht Technology (Vietnam), Co., Ltd.	
	Lot_A9H_CN, Bau Bang Industrial Park, Bau Bang District, Binh Duong	
	Province, Vietnam	
	www.yacht-battery.com	
Transportation Emergency Number	Infotrac (24-Hour Emergency Contact Number)	
	1-800-535-5053 (North America)	
	1-352-323-3500 (International)	
NOTE: The Yacht hatten is considered an article as defined by 20 CEP 1010 1200 (OSHA Hazard Communication Standard). The information		

NOTE: The Yacht battery is considered an article as defined by 29 CFR 1910.1200 (OSHA Hazard Communication Standard). The information contained in this SDS is supplied at the customer's request for information only.

## 2. GHS HAZARD(S) IDENTIFICATION

Health		Physical
Skin corrosion / irritation Category 1		
Series eye damage / eye irritation	Category 1	Corrosive to metals,
Carcinogenicity	Category 1A	Category 1
Specific target organ toxicity, Single exposure	Category 3 Respiratory Tract irritation	

## **GHS Label Elements:**



- May cause cancer.
- May cause respiratory irritation.

#### Precautionary Statements

Prevention	Do not breathe vapor or mist. Wash thoroughly after handling.
Response	If swallowed: Rinse mouth. Do NOT induce vomiting.
	If inhaled: Immediately, remove person to fresh air. If breathing difficulties develop, obtain medical treatment.
	If on skin (or hair): Immediately remove all contaminated clothing. Rinse skin with water / shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a poison center / doctor. Wash contaminated clothing before reuse.
	If exposed or concerned: Get medical advice / attention. Absorb spillage to prevent material damage.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in corrosive resistant container with a resistant inner line. Store locked up.
Disposal	Dispose of contents / container in accordance with local / regional / national / international regulations.



## 3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS (Chemical / Common Names)	CAS Number	% by Weight	
Electrolyte (H <sub>2</sub> SO <sub>4</sub> / H <sub>2</sub> O)	7664-93-9	30-40	
Water	7732-18-5	60-70	

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. FIRST AID MEASURES

Inhalation	IF INHALED: Immediately remove person to fresh air. Immediately call a poison control
	center or doctor for treatment advice.
Skin contact	Immediately take off all contaminated clothing. Rinse skin with water / shower. Call a
	physician or poison control center immediately. Chemical burns must be treated by a
	physician.
Eye contact	Immediately flush eyes for at least 15 minutes. Remove contact lenses if present and easy
	to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. DO not induce
	vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into lungs.
Most important	Burning pain and severe corrosive skin damage. May cause severe irritation or burns to the
symptoms / effects,	eyes, skin, gastrointestinal tract, and respiratory system. Causes serious eye damage.
acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent
	eye damage including blindness could result.
Indication of immediate	Provide general supportive measures and treat symptomatically. Chemical burns: flush
medical attention and	with water immediately. While flushing, remove clothes which do not adhere to affected
special treatment	areas. Call an ambulance. Continue flushing during transport to hospital. Keep victim under
needed	observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions
	to protect themselves.
Self-protection of the	If artificial respiration is required, use a pocket mask equipped with a one-way valve or
first aider	other proper respiratory medical device.

## 5. FIRE FIGHTING MEASURES

Suitable extinguishing media	CO2 ; foam; dry chemical. Trained fire-fighters may use water spray under certain conditions.		
Unsuitable extinguishing media	Do not use water jet as an extinguisher as this will spread the fire.		
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.		
Special protective equipment and precautions for firefighters	Sulfuric acid will not burn, but is capable of igniting finely divided combustible materials on contact. Use dry chemical agents to smother combustible materials. Avoid breathing mists and vapors. Use full protective equipment (acid-resistant bunker gear) and self-contained breathing apparatus.		
Unusual fire and explosion hazards	Battery fluid can evolve flammable hydrogen gas when exposed to metals (such as during charging of lead acid batteries) and may increase the fire risk near sparks, excessive heat or open flames. See Section 10 for list of fire by-products.		
Specific hazards in case of fire	Battery Electrolyte (Sulfuric Acid) is corrosive.		
Additional information	Reacts violently with metals, nitrates, chlorates, carbides and other organic materials. Reacts with most metals to yield explosive flammable hydrogen gas.		



### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective	Keep unnecessary personnel away. Keep people away from and upwind
equipment, and emergency preparedness	of spill / leak. Keep out of low areas. Wear appropriate protective
	equipment and clothing during clean-up. Do not breathe mist or vapor.
	Do not touch damaged containers or spilled material unless wearing
	appropriate protective clothing. Ensure adequate ventilation. Local
	authorities should be advised if significant spillages cannot be
	contained. For personal protection, see section 8 of the SDS. If toxic
	vapors are produced at unknown concentrations, wear a
	NIOSH-approved respirator or SCBA.
Methods and materials for containment	Large spills:
and cleaning up	Stop the flow of material, if this is without risk. Dike the spilled
	material, where this is possible. Cover with plastic sheet to prevent
	spreading. Absorb in vermiculite, dry sand, or earth and place in
	containers. Prevent entry into waterways, sewer, basements or
	confined areas.
	Small spills:
	Wipe up with absorbent material (e.g. cloth, fleece). Clean surface
	thoroughly to remove residual contamination. Use clay, sand, or
	diatomaceous earth.
	Never return spills to original containers for re-use. For waste disposal,
	see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses, or onto the ground.

### 7. HANDLING AND STORAGE

Handling	Do not breathe vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial practices.
Storage	Store locked up. Store in original tightly closed container. Store away from incompatible materials. Keep away from heat, sparks, and open flame. (See section 10 of the SDS)

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Occupational exposure limits (mg/m<sup>3</sup>)

Ingredient	CAS Number	OSHA PEL	ACGIH	US NIOSH	Quebec PEV	Ontario OEL	EU OEL
Sulfuric Acid (Dilute)	7664-93-9	1	0.2	1	1	0.2	0.05 (a)

NOTES:

(a) Thoracic fraction

• OSHA: US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

- ACGIH: US ACGIH Threshold Limit Values
- NIOSH: US NIOSH Pocket Guide to Chemical Hazards

#### **Biological limit values**

No biological exposure limits noted for the ingredient(s).



Engineering Controls (Ventilation)	Good ventilation required (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewashes station.
Personal protective equipmen (Pictograms)	
Respiratory Protection	NONE REQUIRED UNDER NORMAL HANDLING CONDITIONS When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Skin Protection	Wear appropriate chemical resistant gloves and clothing.
Eye Protection	Wear safety glasses with side shields (or goggles). Face shield is recommended.
General Hygiene Considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and / or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid		
Color	Clear / cloudy liquid		
Odor	Slightly acid		
Odor Threshold	Not available		
рН	<1.0		
Melting Point	-79.6 °F / -62 °C		
	Not applicable u	unless individual components exposed.	
Boiling Point	230 °F / 110 °C		
	Not applicable unless individual components exposed.		
Flash Point	Not available		
Evaporation Rate (Butyl Acetate = 1)	Not determined		
Flammability	Not available		
Upper / lower flammability or explosive limits	Fl Hydrogen	lammability Limit Lower – 4 %	
	Fl	lammability Limit Upper – 74 %	
Vapor Pressure (mm Hg @ 20 ° C)	11.7		
Vapor Density	Not available (A	Air = 1)	
Relative Density	1.28 / 1.32		
Solubility	100%		
% Volatile by Weight	0%		
Partition coefficient (n-octanol / water)	Not available		
Auto-ignition temperature	932° F (500°C) (as hydrogen gas)		
Decomposition temperature	Not available		
Viscosity	Not available		



## **10. STABILITY AND REACTIVITY**

Reactivity	This product is stable and non-reactive under normal conditions of use,	
	storage, and transport.	
Stability	Material is stable under normal conditions.	
Conditions to Avoid	Keep away from heat, sparks, open flames, and / or hot surfaces. No smoking.	
	Contact with incompatible materials.	
Incompatibility	Strong reducing agents. Reacts with organic materials. Combustibles. Metals.	
(materials to avoid)	Carbides. Nitrates.	
Hazardous Decomposition Products	Sulfur dioxide (SO <sub>2</sub> ) Sulfur trioxide. Hydrogen.	
Hazardous Polymerization	Will not occur.	

## 11. TOXICOLOGICAL INFORMATION

#### INFORMATION ON LIKELY ROUTES OF EXPOSURE

Inhalation	Corrosive. Inhalation produces damaging effects on the mucous membranes and upper respiratory tract. Inhalation of vapors may cause lung edema. Prolonged inhalation may be harmful.
Skin Contact	Causes severe skins burns. Prolonged skin contact may cause dermatitis.
Eye Contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.
Symptoms related to the	Burning pain and severe corrosive skin damage. May cause severe irritation or burns to
physical, chemical, and	the eyes, skin, gastrointestinal tract, and respiratory system. Causes serious eye
toxicological characteristics	damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
	Permanent eye damage including blindness could result.

#### INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Effects	Occupational exposure to the substance or mixture may cause adverse effects.
Chronic Effects	Prolonged inhalation may be harmful. Sulfuric acid fumes: Prolonged, repeated exposure to acid
	fumes / mists may cause chronic bronchitis, irritation of skin, mucous membranes and
	gastrointestinal tract and erosion of the teeth.

#### **Toxicological Data**

Constituents	Sulfuric Acid absorbed in glass-fiber material (CAS 7664-93-9)	
Species	Rat	
Test Results	2140 mg/kg	510 mg/m3
Acute oral toxicity	LD50	LC50
Skin corrosion / irritation	Causes severe skin burns	
Serious eye damage / eye irritation	Causes severe eye damage	
Respiratory Sensitization	No data available	
Skin Sensitization	Not a skin sensitizer	
Germ Cell Mutagenicity	No data available to indicate product or any components present a greater	
	than 0.1% are mutagenic or genotoxic.	

#### CARCINOGENICITY

Mist: May cause cancer by inhalation ACGIH Group A2 (Suspected human carcinogen)

Carcinogenic Effects			
CAS Number IARC NTP			
Sulfuric acid 7664-93-9 Group 1-Carcinogenic Not established			



## • OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050 / 1200)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or
	developmental effects.
Specific target organ toxicity - single exposure	Not classified
Specific target organ toxicity - repeated exposure	Not classified
Aspiration hazard	Not classified

## **12. ECOLOGICAL INFORMATION**

Persistence and degradability	Sulfuric acid is reactive and not very persistent in the ecosystem.	
Bio-Accumulative potential	Very high mobility and solubility indicate very low risk of bioaccumulation.	
(including Mobility)		
Aquatic toxicity (test results	24-hr LC50, fresh water fish (Brachydanio rerio): 82 mg/l	
and comments)	96-hr LOEC, fresh water fish (Cyprinus carpio): 22 mg/l (lowest observable effect	
	concentration)	
Additional Information	No known effects on stratospheric ozone depletion.	
	Volatile organic compounds: 0% (by Volume)	
	Water Endangering Class (WGK): NA	

## **13. DISPOSAL CONSIDERATIONS**

	Г <b>Т</b>
Disposal Instructions	Collect and reclaim or dispose in sealed containers at licensed waste
	disposal site. Dispose of contents / container in accordance with local /
	regional / national / international regulations.
Hazardous waste code	D002: Corrosive waste
	The waste code should be assigned in discussion between the user, the
	producer, and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or lines
	may retain some product residues. This material and its container must be
	disposed of in a safe manner. (see: Disposal Instructions)
Contaminated packaging	Empty containers should be taken to an approved waste handling site for
	recycling or disposal. Since emptied containers may retain product residue,
	follow label warnings even after container is emptied.

#### **14. TRANSPORT INFORMATION**

#### Ground - US-DOT / CAN-TDG / EU-ADR / APEC-ADR

Proper shipping name		Battery fluid, acid	
Hazard class	8	ID number	UN2796
Packing group	11	Labels	Corrosive

#### Aircraft – ICAO-IATA

Proper shipping name		Battery fluid, acid	
Hazard class	8	ID number	UN2796
Packing group	II	Labels	Corrosive

Reference IATA packing instructions Y840, 851, 855



#### Vessel – IMO-IMDG

Proper shipping name		Battery fluid, acid	
Hazard class	8	ID number	UN2796
Packing group	11	Labels	Corrosive

Reference IMDG packing instructions P001.

#### **15. REGULATORY INFORMATION**

#### **US Federal Regulations**

All components are on the U.S. EPA TSCA Inventory List This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

#### TSCA

• TSCA Section 8b Inventory Status

All chemicals comprising this product are either exempt or listed on the TSCA Inventory.

- TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
- Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Sulfuric Acid (Dilute) (CAS 7664-93-9)	LISTED

#### Superfund Amendment and Reauthorization Act of 1986 (SARA)

Hazard Categories	Immediate Hazard – Yes
	Delayed Hazard – No
	Fire Hazard – No
	Pressure Hazard – No
	Reactivity Hazard – No

#### SARA 302 Extremely hazardous substance

Chemical Name	CAS Number	Weight-%	<b>Reportable Quantity</b>	Threshold Planning Quantity
Sulfuric Acid (dilute)	7664-93-9	30-40	1000 lb EPCRA RQ	1000 lb TPQ
Water	7732-18-5	60-70	Not Listed	Not Listed

#### • Section 311/312 Hazard Chemical: Yes

#### • Section 313 (TRI Reporting)

Chemical Name	CAS Number	% by Weight
Sulfuric Acid (Dilute)	7664-93-9	30-40

#### **Other Federal Regulations**

- Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated
- Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Sulfuric Acid (Dilute) (CAS 7664-93-9)



• Safe Drinking Water Act (SDWA)

Not regulated

• Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number Sulfuric Acid (Dilute) (CAS 7664-93-9), 6552

• Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Sulfuric Acid (Dilute) (CAS 7664-93-9), 20 % WV

• DEA Exempt Chemical Mixtures Code Number Sulfuric Acid (Dilute) (CAS 7664-93-9), 6552

#### **US State Regulations**

	US. Massachusetts RTK – Substance List	
Sulfuric Acid (Dilute)	US New Jersey Worker and Community Right-to-know Act	
(CAS 7664-93-9)	US Pennsylvania Worker and Community Right-to-know Law	
	US Rhode Island RTK	

#### • US. California Proposition 65

The following chemicals identified to exist in the finished product as distributed into commerce are known to the State of California to cause cancer, birth defects, or other reproductive harm:

Chemical Name	CAS Number	% by Weight
Strong inorganic acid mists including sulfuric acid	NA	30-40

California Consumer Product Volatile Organic Compound Emissions

#### International Inventories

Country(s) or Region	Inventory Name	On inventory (yes / no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\* A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### • Canadian Domestic Substance List (DSL)

All ingredients remaining in the finished product as distributed into commerce are included on the Domestic Substances List.

#### WHMIS Classifications

Class E: Corrosive materials present at greater than 1%

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the Controlled Products Regulations.

#### NPRI and Ontario Regulation 127/01

This product contains the following chemicals subject to the reporting requirements of Canada NPRI +/or Ont. Reg. 127/01:

Chemical Name	CAS Number	% by Weight
None	NA	NA



#### • European Inventory of Existing Commercial Chemical Substances (EINECS)

All ingredients remaining in the finished product as distributed into commerce are exempt from, or included on, the European Inventory of Exisiting Commercial Chemical Substances.

#### European Communities (EC) Hazard Classification according to directives 67/548/EEC and 1999/45/EC.

Н	Р	
H314	P264, P280, P301+P330+P331, P303+P361+P353, P305+P351+P338	
Relevant H-, P- number	and full text	
Hazard Abbreviations:		
C: Corrosive		
Hazard statements:		
H314: Causes severe ski	in burns and eye damage.	
Precautionary stateme	nts:	
P264: Wash hands thore	oughly after handling.	
P280: Wear protective a	gloves / protective clothing / eye protection / face protection.	
P301+P330+P331:		
IF SWALLOWED: Rinse r	nouth. Do NOT induce vomiting.	
P303+P361+P353:		
IF ON SKIN (or hair): Remove / Immediately remove all contaminated clothing. Rinse skin with water / shower.		
P305+P351+P338:		
IF IN EYES: Rinse cautiously with water for several minutes.		
Remove contact lenses, if present and easy to do. Continue rinsing.		

#### **16. OTHER INFORMATION**

Issue Date	06/01/2015
Revision Date	-
Version #	01
Further information	NFPA Hazard Scale:
	0 = Minimal
	1 = Slight
	2 = Moderate
	3 = Serious
	4 = Severe
NFPA ratings	

#### DISCLAIMER:

This Safety Data Sheet is based upon information and sources available at the time of preparation or revision date. Information in the SDS was obtained from sources which we believe are reliable, but are beyond our direct supervision or control. We make no Warranty of Merchantability, Fitness for any particular purpose or any other Warranty, Expressed or Implied, with respect to such information and we assume no liability resulting from its use. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. It is the obligation of each user of this product to determine the suitability of this product and comply with the requirements of all applicable laws regarding use and disposal of this product. For additional information concerning Yacht Battery Co., Ltd. products or questions concerning the contents of this SDS please contact your Yacht representative.